

Features

- Electronically commutated DC motor
- With polarity reversal and blocking protection
- High output, quiet running
- Connecting wires 300 mm AWG 26
- Speed control
- Signal output

Specification

Rated Voltage	12 VDC
Operating Voltage	7 ... 13.2 V
Rated Speed	6000 rpm
Rated Current	70 mA
Rated Power	840 mW
Max. Airflow	7.24 CFM, 12.3 m ³ /h
Max. Air Pressure	0.12 inch-H ₂ O, 2.92 mm-H ₂ O
Noise	26.1 dBA, 30.1 dBA max.
Wire	3 Leads - 300 mm
Insulation Resistance	10 MOhm min. @ 500 VDC
Dielectric Strength	5 mA max @ 500 VAC 60 Hz 1 min.
Service Life	70000 hours @ 40 °C



Mechanical


Fan Size (See Dimension Drawing in Page 2)	40 x 40 x 10 mm
Frame	Thermoplastic Black / PBT 15% gf of UL94-V0
Fan Blade	Thermoplastic Black / PBT 15% gf of UL94-V0
Bearing	Ball Bearing
Weight	200 g

Environment


Ambient Operating Temperature	-10 ... 70 °C
Storage Temperature	-40 ... 75 °C
Operation Humidity	5 ... 90 % RH
Storage Humidity	5 ... 90 % RH

DC Axial Fan

Drawing



P-Q Curve



Art Nr.

RND 460-00064